



OPTIMUM™ Energetics Systems

Optimizer™ Care & Cleaning

THE
Energetics Systems
26828 Maple Valley Hwy #109
Maple Valley, WA 98038
(888)424-5553, www.EnergeticsSystems.com

THE
Energetics Systems
26828 Maple Valley Hwy #109
Maple Valley, WA 98038
(888)424-5553, www.EnergeticsSystems.com

CARE & CLEANING INSTRUCTIONS

Please read these instructions carefully before using.

Upon completion of each footbath, we recommend the following procedure for cleaning your Optimizer:

Disconnect the Optimizer cord from the power unit and remove the Optimizer from the water. To prevent corrosion, do not allow the Optimizer cord connector to get wet during use or cleaning. If the Optimizer cord connector has gotten wet, DO NOT plug in the connector to the power unit (let the connector dry out first).

Rinse the Optimizer thoroughly with hot water and then spray it with a mild, non-abrasive cleaning solution such as CLR Kitchen/Bathroom Cleaner (yellow spray bottle) or Orange Glow. Use the brush that comes with the system to gently clean off any particulate matter that has adhered to the Optimizer, if necessary. Do not vigorously scrub the wires, soldering points, copper connecting strips, or blue insulating material. This could compromise the connections and affect the operation of the Optimizer. Leave the cleaning solution on the Optimizer for 10 to 15 minutes then rinse again with hot water. (Cleaning solution should not be left on the Optimizer for any long periods of time as it may cause unnecessary wear or damage to its rings or wiring.)

After your Optimizer has been cleaned, we recommend applying a hospital grade disinfectant and again rinse thoroughly with hot water. This is especially advisable if more than one person will be using the Optimizer. One such anti-bacterial product that has been recommended by practitioners is Citrus II, a non-abrasive hospital grade disinfectant. It can be found online at www.quickmedical.com/beaumont/deodorizing_cleaner.html.

Upon completion of the cleaning always allow the Optimizer to air dry for a minimum of one hour before returning it to the storage case. Do not store the Optimizer in a plastic bag as this can result in a moisture build-up due to condensation.

Note: The same products and cleaning procedures that we recommend for the Optimizer can also be used for your footbath tub.

If you see the Optimizer plates developing a whitish build-up of deposits (this happens in some areas depending upon the mineralization in the water supply), soak the Optimizer in white vinegar for about a half hour (or in a 50/50 solution of white vinegar and water for about an hour), then rinse well with hot water. This will usually loosen up the deposits so they can be removed with regular cleaning.

The Optimizer rings should be inspected for deposit build-up after every footbath, as these deposits can sometimes upon mineralization of the water, the health condition of the person taking the footbath, and many other factors, your Optimizer may require a white vinegar soak as often as every one or two baths. At any rate, you should give your Optimizer a white vinegar soak at least every six to seven footbaths.

“Lack of Color”

If you believe you are experiencing a “lack of color” in your footbath water, please follow these steps before calling us:

1. Clean your Optimizer using a non-abrasive cleanser such as CLR or Orange Glow.
2. Soak the Optimizer in white vinegar for at least a half hour or in a 50/50 white vinegar and water solution for at least one hour.
3. Rinse the Optimizer thoroughly with hot water.
4. Run the cleaned Optimizer in a fresh footbath without a person adding **two to three times the amount of salt** (that you normally use) & using **2.7-3.00 Amperage**.

If you believe you are still experiencing problems with your Optimizer, please call your distributor or Energetics Systems.

THE
Energetics Systems

26828 Maple Valley Hwy #109

Maple Valley, WA 98038

(888)424-5553, www.EnergeticsSystems.com